

PVA EGGSHELL

Scope

TROPICAL PREMIUM PVA EGGSHELL is a Pure Acrylic Medium Sheen PVA paint, used for Interior & exterior walls & ceiling. It offers enhanced stain & UV resistance, is easily washable, scrubbable and withstands repeated washing. PREMIUM PVA EGGSHELL provides a long lasting finish, with high durability and colour stability.

Designed Use

- ☐ **Area of Use** : Interior & Exterior
- ☐ **Area of Use** : Concrete, plaster, masonry, gypsum, may also be used on timber.

Technical Data

- ☐ **Premium Quality** : Semi gloss finish, synthetic resin based paint for interior and exterior surfaces.
- ☐ **Finish** : Smooth Satin Finish



- ☐ **Theoretical Spread Rate** :

Recommended dry film thickness per coat		Spread rate
Minimum	25 microns	13.6 m ² /Ltr
Maximum	40 microns	8.5 m ² /Ltr
Typical	30 microns	11.3 m ² /Ltr

- ☐ **Coverage** : 10 to 11m² per liter pre coat. While estimating the practical spread rates, due allowance should be made for surface profile, uneven application, overspray, losses in containers and equipment. Certain colours such as deep colours, may require more than 2 coats to achieve desired result

- ☐ **Drying Time** :

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
25°C	25minutes	35min	
35°C	20minutes	40min	Indefinite
45°C	15minutes	20min	

Storage and Handling

- ☐ **Storage** : Store in cool, dry conditions
- ☐ **Disposal** : Dispose as normal paint e.g. by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.
- ☐
- ☐
- ☐ **Shelf Life** : Upto 12 months

PVA EGGSHELL

Surface Preparation	<p>The performance of this coating is directly related to the degree of surface preparation.</p> <p>Concrete, Plaster, Masonry</p> <p>Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitance. Remove laitance by wire brush or sweep blast.</p> <p>Apply one coat of Tropical Plaster Primer. Allow to dry, followed by Crack Filler as required. Allow to dry. Smoothen the surface with sand paper, and dust down, apply 2 coats of Tropical PVA Eggshell.</p> <p>If the surface is previously painted, ensure that dirt, stain etc and other loose material and contaminants are removed.</p>
Application Method	<p>Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point.</p> <p>Tropical Premium Eggshell is ready to use. No need to dilute.</p> <ul style="list-style-type: none"> <input type="checkbox"/> Brush or Roller : Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended. <input type="checkbox"/> Conventional Spray : Use normal spray equipment. <input type="checkbox"/> Airless Spray : May also be used.
Safety Precautions	<ul style="list-style-type: none"> <input type="checkbox"/> Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. <input type="checkbox"/> Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
First Aid	<ul style="list-style-type: none"> <input type="checkbox"/> Eyes : In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice. <input type="checkbox"/> Skin : Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinner. <input type="checkbox"/> Inhalation : Remove to fresh air, loosen collar and keep patient rested.
Disclaimer	<p>The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.</p>

Technical Consultancy is always available to ensure optimum specification and performance. For full details contact: -



Manufactured by
OG Paints Ltd., P.O. Box – 5549, Limbe, Malawi