

## PVA PLASTER PRIMER

### Scope

TROPICAL PVA PLASTER PRIMER is a water-based, alkali resistant primer for interior and exterior surfaces (cement, concrete, gypsum & masonry). It provides excellent adhesion to the surface and top coat.

### Designed Use

- ☐ Area of Use : Interior & Exterior
- ☐ Area of Use : Concrete, plaster, masonry, gypsum, may also be used on timber.

### Technical Data

- ☐
- ☐ Finish : Smooth, Matt Finish
- ☐ Colour : White
- ☐
- ☐
- ☐ Theoretical Spread Rate :
 

Recommended dry film thickness per coat		Spread rate
Minimum	25 microns	7.2 m <sup>2</sup> /Ltr
Maximum	35 microns	5.1 m <sup>2</sup> /Ltr
Typical	30 microns	6.0 m <sup>2</sup> /Ltr
- ☐ Coverage : 5 to 8m<sup>2</sup> per liter pre coat. While estimating the practical spread rates, due allowance should be made for surface profile, uneven application, overspray, losses in containers and equipment.

- ☐ Drying Time :
 

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
25°C	40minutes	45min	
35°C	30minutes	35min	Indefinite
45°C	25minutes	30min	

### Storage and Handling

- ☐ Storage : Store in cool, dry conditions
- ☐ Disposal : Dispose as normal paint e.g. by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.
- ☐
- ☐
- ☐ Shelf Life : Upto 12 months

## PVA PLASTER PRIMER

<b>Surface Preparation</b>	<p>The performance of this coating is directly related to the degree of surface preparation.</p> <p><b>Concrete, Plaster, Masonry</b></p> <p>Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitance. Remove laitance by wire brush or sweep blast.</p> <p>If the surface is previously painted, ensure that dirt, stain etc and other loose material and contaminants are removed.</p>
<b>Application Method</b>	<p>Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point.</p> <p>Tropical Plaster Primer is ready to use. No need to dilute.</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> <b>Brush</b> : Recommended. Apply an even coat taking care to avoid runs and sags.</li> <li><input type="checkbox"/> <b>Roller</b> : May also be used. Apply an even coat taking care to avoid runs and sags.</li> </ul>
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.</li> <li><input type="checkbox"/> Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.</li> </ul>
<b>First Aid</b>	<ul style="list-style-type: none"> <li><input type="checkbox"/> <b>Eyes</b> : In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.</li> <li><input type="checkbox"/> <b>Skin</b> : Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinner.</li> <li><input type="checkbox"/> <b>Inhalation</b> : Remove to fresh air, loosen collar and keep patient rested.</li> </ul>
<b>Disclaimer</b>	<p>The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.</p>

Technical Consultancy is always available to ensure optimum specification and performance. For full details contact: -



Manufactured by  
OG Paints Ltd., P.O. Box – 5549, Limbe, Malawi